

A-550C100

ON-OFF SWITCH DISCONNECTOR 1P. 250A D3

Code	009A-550C100
EAN	8430892215275

Product description

Cam switch-disconnector, IP20 with 0-1 red front plate 64x64 for panel fixing. 1 pole 250A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 120 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	1
Operational rating (Ie)	250 A
Thermal rating (Ith)	250 A
Wire section flexible	120 mm ²
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	250 A (415 V)
	250 A (500 V)

Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)

Insulating voltage (V~)	690
Insulating voltage (V...)	600



Dummy AC-21A	75 kW (3x230 V)
	132 kW (3x415 V)
	160 kW (3x500 V)

Mixed load AC-22A	75 kW (3x230 V)
	132 kW (3x415 V)
	132 kW (3x500 V)

Motor load AC-23A	75 kW (3x230 V)
	110 kW (3x415 V)

Standard	IEC 60947-3
Handle type	Directo

Connection



Dimensions

