

A-5620000T

CHANGEOVER SWITCH 1-0-2 3P 12A.D0 ANTIMICROBIAL TREATMENT



Code	009A-5620000T
EAN	8430892307734
Product description	Changeover switch IP20. Kit of 1-0-2 front plate with antimicrobial treatment White color RAL 9010 48x48 for panel fixing. 3 poles 12A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data

Customs code	85365080
ETIM code	EC000216?
Package units	1

Technical data

Poles	3
Operational rating (Ie)	12A
Thermal rating (Ith)	16 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm ²
Wire section flexible	2,5 - 6 mm ²
Tightening torque	1,6 Nm
Connection screws	M4

Terminal	
Max. fuse protection (gG/aM)	25/25 A (415 V) 25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V) 6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	400
Dummy AC-21A	3 kW (3x230 V) 7,5 kW (3x415 V) 11 kW (3x500 V)
Mixed load AC-22A	2,2 kW (3x230 V) 5,5 kW (3x415 V) 7,5 kW (3x500 V)
Motor load AC-23A	2,2 kW (3x230 V) 4 kW (3x415 V) 5,5 kW (3x500 V)
UL Electric characteristics	1 hp 1-fase (110-120 V) 1,5 hp 1-fase (220-240 V) 1 hp 3-fase (220-240 V) 2 hp 3-fase (380-415 V) 3 hp 3-fase (440-480 V) 3 hp 3-fase (550-600 V)
Standard	IEC 60947-3 UL 508
Handle type	Directo antimicrobiano

Dimensions

