

A-562A100

CHANGEOVER SWITCH 3P 160A.D3



Code	009A-562A100
EAN	8430892170826
Product description	Changeover cam switch, IP20 with 1-0-2 grey front plate 64x64 for panel fixing. 3 poles 160A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 70 mm ² cable. Compatible with multiple accessories from the A5 series.


Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Package height (mm)	82
Package width (mm)	120
Package length (mm)	220

Technical data

Poles	3
Operational rating (I _e)	160 A
Thermal rating (I _{th})	160 A
Wire section flexible	70 mm ²
Connection screws	M8
Terminal	
Max. fuse protection (gG/aM)	160 A (415 V) 160 A (500 V)
Conditional shortcircuit current (I _{cc})	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	45 kW (3x230 V) 90 kW (3x415 V) 110 kW (3x500 V)
Mixed load AC-22A	45 kW (3x230 V) 90 kW (3x415 V) 90 kW (3x500 V)
Motor load AC-23A	45 kW (3x230 V) 75 kW (3x415 V)
Standard	IEC 60947-3
Handle type	Directo

Connection



Dimensions

