

# A-570C100

CHANGEOVER SWITCH WITHOUT 0 1P. 250A D3

|             |               |
|-------------|---------------|
| <b>Code</b> | 009A-570C100  |
| <b>EAN</b>  | 8430892215312 |

## Product description

Changeover switch, IP20 with 1-2 grey front plate 64x64 for panel fixing. 1 pole 250A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 95 mm<sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

## Logistic data

|               |          |
|---------------|----------|
| Customs code  | 85365080 |
| ETIM code     | EC000216 |
| Package units | 1        |

## Technical data

|                         |                     |
|-------------------------|---------------------|
| Poles                   | 1                   |
| Operational rating (Ie) | 250 A               |
| Thermal rating (Ith)    | 250 A               |
| Wire section flexible   | 120 mm <sup>2</sup> |
| Connection screws       | M8                  |

Terminal



|                              |               |
|------------------------------|---------------|
| Max. fuse protection (gG/aM) | 250 A (415 V) |
|                              | 250 A (500 V) |

|                                        |              |
|----------------------------------------|--------------|
| Conditional shortcircuit current (Icc) | 8 kA (415 V) |
|                                        | 8 kA (500 V) |

|                           |     |
|---------------------------|-----|
| Insulating voltage (V~)   | 690 |
| Insulating voltage (V...) | 600 |


|              |                  |
|--------------|------------------|
| Dummy AC-21A | 75 kW (3x230 V)  |
|              | 132 kW (3x415 V) |
|              | 160 kW (3x500 V) |

|                   |                  |
|-------------------|------------------|
| Mixed load AC-22A | 75 kW (3x230 V)  |
|                   | 132 kW (3x415 V) |
|                   | 132 kW (3x500 V) |

|                   |                  |
|-------------------|------------------|
| Motor load AC-23A | 75 kW (3x230 V)  |
|                   | 110 kW (3x415 V) |

|             |             |
|-------------|-------------|
| Standard    | IEC 60947-3 |
| Handle type | Directo     |

## Connection



## Dimensions

