

A-6316100

CHANGEOVER SWITCH 3P 3 POS.63A.D2

Code	009A-6316100
EAN	8430892105484

Product description

Changeover step switch, IP20 with 0-1-2-3 grey front plate 64x64 for panel fixing. 3 poles 63A. Size D2. Ergonomic screwless quick-mount handle. Connection with cage terminals for 16-50 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data

Customs code	85365080
ETIM code	EC002611
Package units	1

Technical data

Poles	3
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	63/63 A (415 V)
	63/63 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	22 kW (3x230 V)
	45 kW (3x415 V)
	45 kW (3x500 V)
Mixed load AC-22A	18,5 kW (3x230 V)
	37 kW (3x415 V)
	45 kW (3x500 V)
Motor load AC-23A	18,5 kW (3x230 V)
	30 kW (3x415 V)
	37 kW (3x500 V)
UL Electric characteristics	5 hp 1-fase (110-120 V)
	10 hp 1-fase (220-240 V)
	15 hp 3-fase (220-240 V)
	25 hp 3-fase (380-415 V)
	30 hp 3-fase (440-480 V)
	32 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508
Handle type	Directo

Connection

n.º de ref. 631	1	3	5	7	9	11	13	15	17	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47
	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48
1- 0																								
2- 1	x				x		x																	
3- 2			x	x					x															
4- 3		x					x		x															
5-																								
6-																								
7-																								
8-																								
9-																								
10-																								
11-																								
12-																								
x contacto cerrado		↕ contacto cerrado en varias posiciones sin interrupción		↶ retorno de la última posición a la anterior																				

