

AB5524126

ON-OFF SWITCH DISCONNECTOR 3 P.40A WITH UNDERVOLTAGE RELEASE 230 V AC



Code	009AB5524126
EAN	8430892157414
Product description	On-Off switch disconnecter with undervoltage release 230V. Red/yellow padlockable handle panel fixing 66x66. 3 poles 40A. IP20 terminal connection for wires size 1-6 mm².

Logistic data

Customs code	85365080
--------------	----------

Technical data

Poles	3
Operational rating (Ie)	40 A
Thermal rating (Ith)	40 A
Wire section (AWG)	6
Wire section rigid	6 - 25 mm ²
Wire section flexible	6 - 16 mm ²
Tightening torque	2 Nm
Connection screws	M5

Terminal



Max. fuse protection (gG/aM)	40/32 A (415 V) 40/32 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V) 6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	15 kW (3x230 V) 22 kW (3x415 V) 30 kW (3x500 V)
Mixed load AC-22A	11 kW (3x230 V) 22 kW (3x415 V) 22 kW (3x500 V)
Motor load AC-23A	11 kW (3x230 V) 18,5 kW (3x415 V) 22 kW (3x500 V)
Standard	IEC 60947-3 UL 508
Handle type	Bloqueable candados

Connection

