

## AB5530000T

SWITCH 4P 12A.D0 PADLOCKABLE HANDLE RED/YELLOW ANTIMICROBIAL TREATMENT



<b>Code</b>	009AB5530000T
<b>EAN</b>	8430892307932
<b>Product description</b>	Padlockable On-off switch disconnecter with antimicrobial treatment. Red handle/yellow front plate 64x64 for panel fixing. 4 poles 12A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

## Logistic data

Customs code	85365080
ETIM code	EC000216?
Package units	1

## Technical data

Poles	4
Operational rating (Ie)	12A
Thermal rating (Ith)	16 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm <sup>2</sup>
Wire section flexible	2,5 - 6 mm <sup>2</sup>
Tightening torque	1,6 Nm
Connection screws	M4

Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
	400
Dummy AC-21A	3 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)
Mixed load AC-22A	2,2 kW (3x230 V)
	5,5 kW (3x415 V)
	7,5 kW (3x500 V)
Motor load AC-23A	2,2 kW (3x230 V)
	4 kW (3x415 V)
	5,5 kW (3x500 V)
UL Electric characteristics	1 hp 1-fase (110-120 V)
	1,5 hp 1-fase (220-240 V)
	1 hp 3-fase (220-240 V)
	2 hp 3-fase (380-415 V)
	3 hp 3-fase (440-480 V)
	3 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508
Handle type	Bloqueable candados

**Dimensions**

