

AC552A100

ON-OFF SWITCH DISCONNECTOR 3P.160A.D3 PADLOCKABLE BLACK/GREY

Code	009AC552A100
EAN	8430892171588

Product description

Padlockable on-off switch disconnecter,IP20 with black handle/grey front plate 64x64 for panel fixing. 3 poles 160A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 70 mm² cable. Compatible with multiple accessories from the A5 series.

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	3
Operational rating (Ie)	160 A
Thermal rating (Ith)	160 A
Wire section flexible	70 mm ²
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	160 A (415 V)
	160 A (500 V)

Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)

Insulating voltage (V~)	690
Insulating voltage (V...)	600

Dummy AC-21A	45 kW (3x230 V)
	90 kW (3x415 V)
	110 kW (3x500 V)

Mixed load AC-22A	45 kW (3x230 V)
	90 kW (3x415 V)
	90 kW (3x500 V)

Motor load AC-23A	45 kW (3x230 V)
	75 kW (3x415 V)

Standard	IEC 60947-3
Handle type	Bloqueable candados

Connection



Dimensions

