

## A-550112L

COMBILIGHT ON-OFF SWITCH RED/GREEN 230V 1P 16A



|                            |                                                                                                                                                                                                                                                                                                                               |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Code</b>                | 009A-550112L                                                                                                                                                                                                                                                                                                                  |
| <b>EAN</b>                 | 8430892256995                                                                                                                                                                                                                                                                                                                 |
| <b>Product description</b> | Combilight switch disconnecter by position 230vac, IP20 with 0-1 black front plate 48x48 for panel fixing, 0" red LED, "1" green LED. 1 pole 16A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series. " |

## Logistic data

|               |          |
|---------------|----------|
| Customs code  | 85365080 |
| ETIM code     | EC000216 |
| Package units | 1        |

## Technical data

|                         |                         |
|-------------------------|-------------------------|
| Operational rating (Ie) | 16 A                    |
| Thermal rating (Ith)    | 20 A                    |
| Wire section (AWG)      | 10                      |
| Wire section rigid      | 2,5 - 6 mm <sup>2</sup> |
| Wire section flexible   | 2,5 - 6 mm <sup>2</sup> |
| Tightening torque       | 1,6 Nm                  |
| Connection screws       | M4                      |

### Terminal



|                                        |                           |
|----------------------------------------|---------------------------|
| Max. fuse protection (gG/aM)           | 25/25 A (415 V)           |
|                                        | 25/25 A (500 V)           |
| Conditional shortcircuit current (Icc) | 6 kA (415 V)              |
|                                        | 6 kA (500 V)              |
| Insulating voltage (V~)                | 690                       |
| Insulating voltage (V...)              | 400                       |
| Dummy AC-21A                           | 5,5 kW (3x230 V)          |
|                                        | 11 kW (3x415 V)           |
|                                        | 15 kW (3x500 V)           |
| Mixed load AC-22A                      | 4 kW (3x230 V)            |
|                                        | 7,5 kW (3x415 V)          |
|                                        | 11 kW (3x500 V)           |
| Motor load AC-23A                      | 3 kW (3x230 V)            |
|                                        | 5,5 kW (3x415 V)          |
|                                        | 7,5 kW (3x500 V)          |
| UL Electric characteristics            | 1,5 hp 1-fase (110-120 V) |
|                                        | 2 hp 1-fase (220-240 V)   |
|                                        | 2 hp 3-fase (220-240 V)   |
|                                        | 2 hp 3-fase (380-415 V)   |
|                                        | 3 hp 3-fase (440-480 V)   |
|                                        | 5 hp 3-fase (550-600 V)   |
| Standard                               | IEC 60947-3               |
|                                        | UL 508                    |

Connection

---

