

A-553412L4

COMBILIGHT ON-OFF SWITCH RED/GREEN 400V 4P 40A



Code	009A-553412L4
EAN	8430892262521
Product description	Combilight switch disconnecter by position 400vac, IP20 with 0-1 black front plate 64x64 for panel fixing, 0" red LED, "1" green LED. 4 poles 40A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 6-16 mm ² cable. Compatible with multiple accessories from the A5 series. "

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1
Package height (mm)	155
Package width (mm)	70
Package length (mm)	70

Technical data

Operational rating (Ie)	40 A
Thermal rating (Ith)	40 A
Wire section (AWG)	6
Wire section rigid	6 - 25 mm ²
Wire section flexible	6 - 16 mm ²
Tightening torque	2 Nm
Connection screws	M5

Terminal



Max. fuse protection (gG/aM)	40/32 A (415 V)
	40/32 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	15 kW (3x230 V)
	22 kW (3x415 V)
	30 kW (3x500 V)
Mixed load AC-22A	11 kW (3x230 V)
	22 kW (3x415 V)
	22 kW (3x500 V)
Motor load AC-23A	11 kW (3x230 V)
	18,5 kW (3x415 V)
	22 kW (3x500 V)
UL Electric characteristics	2 hp 1-fase (110-120 V)
	5 hp 1-fase (220-240 V)
	7,5 hp 3-fase (220-240 V)
	10 hp 3-fase (380-415 V)
	15 hp 3-fase (440-480 V)
	20 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508

Connection

7	8		×
5	6		×
3	4		×
1	2		×
553		0	1

