

## A-562612L4

COMBILIGHT CHANGEOVER SWITCH RED/GREEN 400V 3P 63A



|                            |                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Code</b>                | 009A-562612L4                                                                                                                                                                                                                                                                                                                                  |
| <b>EAN</b>                 | 8430892262811                                                                                                                                                                                                                                                                                                                                  |
| <b>Product description</b> | Combilight changeover switch by position 400vac, IP20 with 1-0-2 64x64 black front plate for panel fixing, 1" green LED, "0" red LED, "2" green LED.. 3 poles 63A. Size D2. Ergonomic screwless quick-mount handle. Connection with cage terminals for 16-50 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series. " |

## Logistic data

|                     |          |
|---------------------|----------|
| Customs code        | 85365080 |
| ETIM code           | EC000216 |
| Package units       | 1        |
| Package height (mm) | 163      |
| Package width (mm)  | 88       |
| Package length (mm) | 86       |

## Technical data

|                         |                         |
|-------------------------|-------------------------|
| Operational rating (Ie) | 63 A                    |
| Thermal rating (Ith)    | 70 A                    |
| Wire section (AWG)      | 16 - 1                  |
| Wire section flexible   | 16 - 50 mm <sup>2</sup> |
| Tightening torque       | 3,5 Nm                  |
| Connection screws       | M8                      |

### Terminal



|                                        |                                                                                                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. fuse protection (gG/aM)           | 63/63 A (415 V)<br>63/63 A (500 V)                                                                                                                                  |
| Conditional shortcircuit current (Icc) | 8 kA (415 V)<br>8 kA (500 V)                                                                                                                                        |
| Insulating voltage (V~)                | 690                                                                                                                                                                 |
| Insulating voltage (V...)              | 600                                                                                                                                                                 |
| Dummy AC-21A                           | 22 kW (3x230 V)<br>45 kW (3x415 V)<br>45 kW (3x500 V)                                                                                                               |
| Mixed load AC-22A                      | 18,5 kW (3x230 V)<br>37 kW (3x415 V)<br>45 kW (3x500 V)                                                                                                             |
| Motor load AC-23A                      | 18,5 kW (3x230 V)<br>30 kW (3x415 V)<br>37 kW (3x500 V)                                                                                                             |
| UL Electric characteristics            | 5 hp 1-fase (110-120 V)<br>10 hp 1-fase (220-240 V)<br>15 hp 3-fase (220-240 V)<br>25 hp 3-fase (380-415 V)<br>30 hp 3-fase (440-480 V)<br>32 hp 3-fase (550-600 V) |
| Standard                               | IEC 60947-3<br>UL 508                                                                                                                                               |

## Connection

|     |    |   |   |   |
|-----|----|---|---|---|
| 11  | 12 |   |   | × |
| 9   | 10 | × |   |   |
| 7   | 8  |   |   | × |
| 5   | 6  | × |   |   |
| 3   | 4  |   |   | × |
| 1   | 2  | × |   |   |
| 562 |    | 1 | 0 | 2 |

