

## ACA-63/2-160DP

AC THREE PHASE COMBINER BOX 400V AC 3P+N, INPUT 2 INVERTERS 63A, OUTPUT 160A , WITH METAL ENCLOSURE



**Code**

029ACA-63/2-160DP

---

## Combiner box technical data

|                                  |                  |
|----------------------------------|------------------|
| Breaking capacity EN 60898-1     | 6kA / 40kA       |
| Combiner type                    | AC               |
| Inverter AC output               | 3P+N             |
| Voltage                          | 415 V AC         |
| Surge protector                  | Class II         |
| Diferential type                 | 30mA             |
| Group                            | 2                |
| Incoming current rating          | 63 A             |
| Outgoing current rating          | 160 A            |
| Incoming breaking capacity       | 6 kA             |
| Outgoing breaking capacity       | 40 kA            |
| Surge protector code             | PSTC440          |
| Surge protector type             | II               |
| Nominal discharge current (In)   | 20 kA            |
| Maximum discharge current (Imax) | 40 kA            |
| Protection level at In (Up)      | 1.5 kV           |
| Ingress protection IP            | IP66             |
| Impact protection IK             | IK10             |
| Standards                        | IEC EN 61439-1/2 |

## Dimensions

|                |        |
|----------------|--------|
| Product height | 600 mm |
| Product width  | 600 mm |
| Product length | 250 mm |

## Connection

