

## AC552B107

ON-OFF SWITCH 3P.200A. STEEL ENCLOSURE



|                            |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Code</b>                | 009AC552B107                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>EAN</b>                 | 8430892163521                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Product description</b> | 3-pole 200A safety switch in IP65 enclosure. E2 sheet steel enclosure suitable for indoor or outdoor use in RAL7035 grey color, dimensions 250x300x200. High impact resistance IK10. Base mounted switch with extended shaft and interlock in closed position. Black / grey padlockable handle (up to 4 padlocks of 8mm diameter). Earthing terminal. Cable lug terminal connection for 90 mm <sup>2</sup> cable |

Logistic data

|               |          |
|---------------|----------|
| Customs code  | 85365080 |
| ETIM code     | EC000216 |
| Package units | 1        |

Technical data

|                         |                    |
|-------------------------|--------------------|
| Poles                   | 3                  |
| Operational rating (Ie) | 200 A              |
| Thermal rating (Ith)    | 200 A              |
| Wire section flexible   | 95 mm <sup>2</sup> |
| Connection screws       | M8                 |

|                                        |                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------|
| Terminal                               |  |
| Max. fuse protection (gG/aM)           | 200 A (415 V)<br>200 A (500 V)                                                      |
| Conditional shortcircuit current (Icc) | 8 kA (415 V)<br>8 kA (500 V)                                                        |
| Insulating voltage (V~)                | 690                                                                                 |
| Insulating voltage (V...)              | 600                                                                                 |
| Dummy AC-21A                           | 55 kW (3x230 V)<br>110 kW (3x415 V)<br>132 kW (3x500 V)                             |
| Mixed load AC-22A                      | 55 kW (3x230 V)<br>110 kW (3x415 V)<br>110 kW (3x 500 V)                            |
| Motor load AC-23A                      | 55 kW (3x230 V)<br>90 kW (3x415 V)                                                  |
| Standard                               | IEC 60947-3                                                                         |
| Enclosure type                         | METAL                                                                               |

Connection



## Dimensions

---

