

AC553C107

ON-OFF SWITCH 4P.250A. IP65 ENCLOSURE



Code	009AC553C107
EAN	8430892235488
Product description	4-pole 250A safety switch in IP65 enclosure. E2 sheet steel enclosure suitable for indoor or outdoor use in RAL7035 grey color, dimensions 250x300x200. High impact resistance IK10. Base mounted switch with extended shaft and interlock in closed position. Black / grey padlockable handle (up to 4 padlocks of 8mm diameter). Earthing terminal. Cable lug terminal connection for 110 mm ² cable

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	4
Operational rating (Ie)	250 A
Thermal rating (Ith)	250 A
Wire section flexible	120 mm ²
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	250 A (415 V)
	250 A (500 V)

Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)

Insulating voltage (V~)	690
Insulating voltage (V...)	600



Dummy AC-21A	75 kW (3x230 V)
	132 kW (3x415 V)
	160 kW (3x500 V)

Mixed load AC-22A	75 kW (3x230 V)
	132 kW (3x415 V)
	132 kW (3x500 V)

Motor load AC-23A	75 kW (3x230 V)
	110 kW (3x415 V)

Standard	IEC 60947-3
Enclosure type	METAL

Connection



Dimensions

