

L475J6100

LD BYPASS CHANGEOVER SWITCH 3P+6P 63A WITH OVERLAPPING

Code

009L475J6100

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	3
Auxiliary	1NO
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	63/63 A (415 V)
	63/63 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	22 kW (3x230 V)
	45 kW (3x415 V)
	45 kW (3x500 V)
Mixed load AC-22A	18,5 kW (3x230 V)
	37 kW (3x415 V)
	45 kW (3x500 V)
Motor load AC-23A	18,5 kW (3x230 V)
	30 kW (3x415 V)
	37 kW (3x500 V)
Standard	IEC 60947-3

Connection

n.º de ref. 475J Coaxial	L1 3		F 5		E 7		L2 9		L3 13		15		17 19		G 21 23		25 27		29 31		33 35		37 39		41 43		45 47	
	A 2 4		S1 6		S2 8		10 12		B 14		C 16		S3 18 20		22 24		26 28		30 32		34 36		38 40		42 44		46 48	
1- I	X		X	X			X	X				X																
2- I + AUX	X		X	X			X	X				X	X															
3- I+II+AUX	X	X	X	X			X	X				X	X															
4- II+AUX		X					X					X		X														
5-																												
6-																												
7-																												
8-																												
9-																												
10-																												
11-																												
12-																												
X contacto cerrado		X contacto cerrado en varias posiciones sin interrupción		↪ retorno de la última posición a la anterior																								



Dimensions

