

L479J9100

BYPASS LD CHANGEOVER SWITCH 4P+8P 125A +AC WITH OVERLAPPING

Code

009L479J9100

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	4
Auxiliary	1NO
Operational rating (Ie)	125 A
Thermal rating (Ith)	125 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	125/100 A (415 V)
	125/100 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	37 kW (3x230 V)
	75 kW (3x415 V)
	90 kW (3x500 V)
Mixed load AC-22A	37 kW (3x230 V)
	55 kW (3x415 V)
	75 kW (3x500 V)
Motor load AC-23A	30 kW (3x230 V)
	55 kW (3x415 V)
	55 kW (3x500 V)
Standard	IEC 60947-3

Connection

n.º de ref.	L1		F		E		L2		L3		H		N																			
479J	1	3	5	7	9	11	13	15	17	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47								
Coaxial	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48								
1- I	X		X	X	X		X	X	X	X	X	X																				
2- I+AUX	X		X	X	X		X	X	X	X	X	X																				
3- I+II+AUX	X	X	X	X		X	X	X	X	X	X	X	X	X																		
4- II+AUX		X			X				X		X		X																			
5-																																
6-																																
7-																																
8-																																
9-																																
10-																																
11-																																
12-																																

X contacto cerrado

X contacto cerrado en varias posiciones sin interrupción

↩ retorno de la última posición a la anterior



Dimensions

