

# LC5436107

LD CHANGEOVER SWITCH I - I+II - II 4P 63A ENCLOSED

**Code**

009LC5436107

**EAN**

8430892353885

## Logistic data

|                     |          |
|---------------------|----------|
| Customs code        | 85365080 |
| ETIM code           | EC000216 |
| Package units       | 1        |
| Package height (mm) | 150      |
| Package width (mm)  | 170      |
| Package length (mm) | 205      |

## Technical data

|                         |                         |
|-------------------------|-------------------------|
| Poles                   | 4                       |
| Auxiliary               | -                       |
| Operational rating (Ie) | 63 A                    |
| Thermal rating (Ith)    | 70 A                    |
| Wire section (AWG)      | 16 - 1                  |
| Wire section flexible   | 16 - 50 mm <sup>2</sup> |
| Tightening torque       | 3,5 Nm                  |
| Connection screws       | M8                      |

### Terminal



|                                        |                                                         |
|----------------------------------------|---------------------------------------------------------|
| Max. fuse protection (gG/aM)           | 63/63 A (415 V)<br>63/63 A (500 V)                      |
| Conditional shortcircuit current (Icc) | 8 kA (415 V)<br>8 kA (500 V)                            |
| Insulating voltage (V~)                | 690                                                     |
| Insulating voltage (V...)              | 600                                                     |
| Dummy AC-21A                           | 22 kW (3x230 V)<br>45 kW (3x415 V)<br>45 kW (3x500 V)   |
| Mixed load AC-22A                      | 18,5 kW (3x230 V)<br>37 kW (3x415 V)<br>45 kW (3x500 V) |
| Motor load AC-23A                      | 18,5 kW (3x230 V)<br>30 kW (3x415 V)<br>37 kW (3x500 V) |
| Standard                               | IEC 60947-3                                             |

## Dimensions

---

