

LD9939100

BYPASS LD CHANGEOVER SWITCH 3P+6P 125A WITH OVERLAPPING

Code

009LD9939100

EAN

8430892335973

Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	3
Operational rating (Ie)	125 A
Thermal rating (Ith)	125 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	125/100 A (415 V) 125/100 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V) 8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	37 kW (3x230 V) 75 kW (3x415 V) 90 kW (3x500 V)
Mixed load AC-22A	37 kW (3x230 V) 55 kW (3x415 V) 75 kW (3x500 V)
Motor load AC-23A	30 kW (3x230 V) 55 kW (3x415 V) 55 kW (3x500 V)
Standard	IEC 60947-3

Connection

993

The diagram shows a 20x20 grid. The top 10 rows (rows 1-10) are shaded gray. The bottom 10 rows (rows 11-20) are white. The columns are numbered 1 to 20 at the top. Red lines connect circles at the following coordinates (row, column): (1,1)-(1,2), (1,10)-(1,11), (1,18)-(1,19), (2,2)-(2,3), (2,4)-(2,5), (2,6)-(2,7), (2,8)-(2,9), (2,10)-(2,11), (2,12)-(2,13), (2,14)-(2,15), (2,16)-(2,17), (2,18)-(2,19), and (2,20)-(2,21). Below the grid is a table with 3 rows and 10 columns.

I	×		×	×		×	×		×
I+II	×	×	×	×	×	×	×		×
II		×			×			×	

Dimensions

