

LDA62B100

LD CHANGEOVER SWITCH 3P 200A +AC

Code	009LDA62B100
EAN	8430892215558


Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

Technical data

Poles	3
Auxiliary	1NO
Operational rating (Ie)	200 A
Thermal rating (Ith)	200 A
Wire section flexible	95 mm ²
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	200 A (415 V)
	200 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	55 kW (3x230 V)
	110 kW (3x415 V)
	132 kW (3x500 V)
Mixed load AC-22A	55 kW (3x230 V)
	110 kW (3x415 V)
	110 kW (3x 500 V)
Motor load AC-23A	55 kW (3x230 V)
	90 kW (3x415 V)
Standard	IEC 60947-3

Connection

A diagram showing a 3x3 grid of numbers 1 through 12. The numbers are arranged in three rows and three columns. The first row contains 1, 3, 5, 7, 9, 11. The second row contains 2, 4, 6, 8, 10, 12. The third row contains 13, 15, 14, 16. Red X's are placed in the first row (1, 3, 5, 7, 9, 11) and the second row (2, 4, 6, 8, 10, 12). To the right of the 3x3 grid is a 4x4 grid of numbers 13 through 16. The numbers are arranged in four rows and four columns. The first row contains 13, 15. The second row contains 14, 16. The third row contains 17, 19, 18, 20. The fourth row contains 21, 23, 22, 24. Red X's are placed in the first row (13, 15) and the second row (14, 16).

Dimensions

