

YL3926301

MULTIPLE SOURCE MOTORISED CHANGEOVER SWITCH 3P 63A 230VAC



Code	007YL3926301
EAN	8430892250962
Product description	Three sources motorised changeover switch 1-0-2-3 , 3 poles 63A with motor unit supply 80-230Vac . Size D2 dimensions 147x193x113, includes auxiliary contact 12A. Back plate mounting. Built-in internal links, mechanical and electrical interlock. Local emergency operation, includes removable padlockable handle. Display for switch position indication and operation counter.Impulse control logic. Protection against supply voltage failure . Cable clamp connection for wires 16-50mm ² .

Logistic data

Customs code	85365080
ETIM code	EC000216

Technical data

Rated voltage / frequency	690 V / 50 Hz
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire cross section	16-50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Peak consumption	2,5 A
Nominal consumption	40 mA
Weight	2250 gr
Supply voltage (V DC)	12 V +15%
Standard	IEC 60947-3
Y5 Type	39
Supply	80-230V AC

Connection

C. Aux

392

		1	3	5	7	9	11	13	15	17	19	21	23	25	27
		○	○	○	○	○	○	○	○	○	○	○	○	○	○
		○	○	○	○	○	○	○	○	○	○	○	○	○	○
		2	4	6	8	10	12	14	16	18	20	22	24	26	28

Diagram illustrating the construction of the 32-bit auxiliary register (Aux) for the first round of DES encryption. The top row shows the initial permutation of the 32 bits, with the first 16 bits (1-16) being the original plaintext and the last 16 bits (17-32) being the original ciphertext. The bottom row shows the result after the first round of encryption, where the first 16 bits are the original ciphertext and the last 16 bits are the original plaintext. The red line indicates the swap of the two halves.