

YL5539301

MOTORISED SWITCH 4P 125A. 80-230VAC



Code	007YL5539301
EAN	8430892213516
Product description	Motorised switch-disconnector 0-1 , 4 poles 125A with motor unit supply 80-230Vac . Size D2 dimensions 147x162x113, includes auxiliary contact 12A. Back plate mounting. Local emergency operation, includes removable padlockable handle. Display for switch position indication and operation counter. Impulse control logic. Protection against supply voltage failure . Cable clamp connection for wires 16-50mm².

Logistic data

Customs code	85365080
ETIM code	EC000216

Technical data

Rated voltage / frequency	690 V / 50 Hz
Operational rating (Ie)	125 A
Thermal rating (Ith)	125 A
Wire cross section	16-50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Peak consumption	2,5 A
Nominal consumption	40 mA
Weight	2250 gr
Supply voltage (V DC)	12 V +15%
Standard	IEC 60947-3
Supply	80-230V AC

Connection

C. Aux.

553

	1	3	5	7		17	19
	○	○	○	○		○	○
	○	○	○	○		○	○
	2	4	6	8		18	20
0							
1	×	×	×	×	×		

Dimensions

